



## Sample Written Exposure Control Plan

**Company:**

John Doe Renovators

**Person Completing the Plan, Title:**

John Doe, Owner

**Description of Task:**

Demolishing concrete and tile floors inside homes or public buildings using a jackhammer.

**Control Description**

Controls:

- Use jackhammer equipped with the appropriate, commercially available shroud and a vacuum dust collection system with the flow rate recommended by the jackhammer manufacturer, a filter that is at least 99 percent efficient, and a filter cleaning mechanism.
- Use a portable fan to exhaust air and prevent the buildup of dust.

Work practices:

- Check shrouds and hoses to make sure they are not damaged before starting work.
- Make sure the hoses do not become kinked or bent while working.
- Use switch on vacuum to activate filter cleaning at the frequency recommended by the manufacturer.
- Replace vacuum bags as needed to prevent overfilling.
- Use the jackhammer and vacuum controls according to manufacturer's instructions for reducing the release of visible dust.
- If visible dust increases, check controls and adjust as needed.

Respiratory protection:

- Use respirator with APF of 10 the entire time the task is being performed.
- See the written respiratory protection program for information on selection, training and fit testing requirements, in addition to proper use instructions for respirators (for example, being clean shaven when using a respirator that seals against the face).

**Housekeeping:**

- Dust containing silica on work surfaces and equipment must be cleaned up using wet methods or a HEPA-filtered vacuum.
- Do not use compressed air or dry sweeping for removing dust and debris containing silica from work surfaces.
- Dispose of used vacuum bags in a container and keep the container sealed.

**Procedures Used to Restrict Access to Work Areas:**

Schedule the work so that only employees who are engaged in the task (the jackhammer operator and employees helping the operator) are in the area.